

## 4.06 Poleas casquillo cónico tipo H

### Poleas dentadas con casquillo cónico

#### H 100 Paso 1/2" (12,7 mm)

Material	CODIGO	TIPO	DIENTES	CASQUILLO	INTERIOR MAXIMO	Dp	De	Df	Dm	Di	F	L	R	N.º VALONA	Kg.
ACERO	TL 16 H 100	16 F	16	1108	28	64,68	63,31	71	-	45	31,0	22,0	9,0	311	0,42
	TL 18 H 100	16 F	18	1210	35	72,77	71,39	79	-	52	31,0	25,0	6,0	313	0,49
	TL 19 H 100	16 F	19	1210	35	76,81	75,44	83	-	56	31,0	25,0	6,0	314	0,62
	TL 20 H 100	16 F	20	1210	35	80,85	79,48	87	-	60	31,0	25,0	6,0	315	0,73
	TL 21 H 100	16 F	21	1210	35	84,89	83,52	91	-	64	32,0	25,0	7,0	316	0,80
	TL 22 H 100	16 F	22	1210	35	88,94	87,56	93	-	67	32,0	25,0	7,0	317	0,94
	TL 23 H 100	16 F	23	1210	42	92,98	91,61	97	-	70	32,0	25,0	7,0	318	0,97
	TL 24 H 100	16 F	24	1610	42	97,02	95,65	103	-	73,5	32,0	25,0	7,0	320	1,05
	TL 25 H 100	16 F	25	1610	42	101,06	99,69	106	-	77	32,0	25,0	7,0	321	1,10
	TL 26 H 100	16 F	26	1610	42	105,11	103,73	111	-	82	32,0	25,0	7,0	322	1,20
	TL 27 H 100	16 F	27	1610	42	109,15	107,78	115	-	85	32,0	25,0	7,0	323	1,35
	TL 28 H 100	16 F	28	1610	42	113,19	118,82	119	-	90,5	32,0	25,0	7,0	325	1,50
	TL 30 H 100	16 F	30	1610	42	121,28	119,90	127	-	98	32,0	25,0	7,0	327	1,78
	TL 32 H 100	17 F	32	1610	42	129,36	127,99	135	90	106	32,0	25,0	7,0	328	2,05
	TL 36 H 100	17 F	36	1610	42	145,53	144,16	152	92	121	32,0	25,0	7,0	334	2,80
	TL 40 H 100	17 F	40	1610	42	161,70	160,33	168	92	138	32,0	25,0	7,0	338	3,65
	TL 44 H 100	21 F	44	2012	50	177,87	176,50	184	102	152	32,0	32,0	-	339	3,86
	TL 48 H 100	21 F	48	2012	50	194,04	192,67	200	106	169	32,0	32,0	-	342	4,20
FUNDICION	TL 60 H 100	20	60	2012	50	242,55	241,18	-	106	223	34,0	32,0	1,0	-	-
	TL 72 H 100	20	72	2012	50	291,06	289,69	-	106	270	34,0	32,0	1,0	-	-
	TL 84 H 100	20	84	2012	50	339,57	338,20	-	106	320	34,0	32,0	1,0	-	-
	TL 96 H 100	14	96	2517	60	388,08	386,71	-	119	366	34,0	45,0	5,5	-	-
	TL 120 H 100	14	120	2517	60	485,10	483,73	-	119	462	34,0	45,0	5,5	-	-

#### H 150 Paso 1/2"

Material	CODIGO	TIPO	DIENTES	CASQUILLO	INTERIOR MAXIMO	Dp	De	Df	Dm	Di	F	L	R	N.º VALONA	Kg.
ACERO	TL 18 H 150	16 F	18	1210	35	72,77	71,39	79	-	52	45,0	25,0	20,0	313	0,60
	TL 19 H 150	16 F	19	1210	35	76,81	75,44	83	-	56	45,0	25,0	20,0	314	0,72
	TL 20 H 150	16 F	20	1210	35	80,85	79,48	87	-	60	45,0	25,0	20,0	315	0,83
	TL 21 H 150	16 F	21	1210	35	84,89	83,52	91	-	64	45,0	25,0	20,0	316	1,00
	TL 22 H 150	16 F	22	1210	35	88,94	87,56	93	-	67	45,0	25,0	20,0	317	1,25
	TL 23 H 150	16 F	23	1610	42	92,98	91,61	97	-	70	45,0	25,0	20,0	318	1,05
	TL 24 H 150	16 F	24	1610	42	97,02	95,65	103	-	73,5	45,0	25,0	20,0	320	1,10
	TL 25 H 150	16 F	25	1610	42	101,06	99,69	106	-	77	45,0	25,0	20,0	321	1,30
	TL 26 H 150	16 F	26	1610	42	105,11	103,73	111	-	82	45,0	25,0	20,0	322	1,42
	TL 27 H 150	16 F	27	1610	42	109,15	107,78	115	-	85	45,0	25,0	20,0	323	1,65
	TL 28 H 150	16 F	28	1610	42	113,19	111,82	119	-	90,5	45,0	25,0	20,0	325	1,88
	TL 30 H 150	16 F	30	1610	42	121,28	119,90	127	-	98	45,0	25,0	20,0	327	2,05
	TL 32 H 150	17 F	32	1610	42	129,36	127,99	135	90	106	45,0	25,0	20,0	328	2,35
	TL 36 H 150	17 F	36	1610	42	145,53	144,16	152	92	121	45,0	25,0	20,0	334	3,20
	TL 40 H 150	17 F	40	1610	42	161,70	160,33	168	92	138	45,0	25,0	20,0	338	4,10
	TL 44 H 150	17 F	44	2012	50	177,87	176,50	184	106	152	45,0	32,0	13,0	339	4,50
	TL 48 H 150	17 F	48	2012	50	194,04	192,67	200	106	169	45,0	32,0	13,0	342	4,80
	FUNDICION	TL 60 H 150	20	60	2012	50	242,55	241,18	-	106	223	46,0	32,0	7,0	-
TL 72 H 150		20	72	2012	50	291,06	289,69	-	106	270	46,0	32,0	7,0	-	-
TL 84 H 150		20	84	2012	50	339,57	338,20	-	106	320	46,0	32,0	7,0	-	-
TL 96 H 150		20	96	2517	60	388,08	386,71	-	119	366	46,0	45,0	0,5	-	-
TL 120 H 150		20	120	2517	60	485,10	483,73	-	119	462	46,0	45,0	0,5	-	-

## Poleas dentadas con casquillo cónico

### H 200 Paso 1/2" (12,7 mm)

Material	CODIGO	TIPO	DIENTES	CASQUILLO	INTERIOR MAXIMO	Dp	De	Df	Dm	Di	F	L	R	N.º VALONA	Kg.
ACERO	TL 18 H 200	16 F	18	1210	35	72,77	71,39	79	-	52	58,0	25,0	33,0	313	
	TL 19 H 200	16 F	19	1210	35	76,81	75,44	83	-	56	58,0	25,0	33,0	314	
	TL 20 H 200	16 F	20	1610	42	80,85	79,48	87	-	60	58,0	25,0	33,0	315	
	TL 21 H 200	16 F	21	1610	42	84,89	83,52	91	-	64	58,0	25,0	33,0	316	
	TL 22 H 200	16 F	22	1610	42	88,94	87,56	93	-	67	58,0	25,0	33,0	317	
	TL 23 H 200	16 F	23	1610	42	92,98	91,61	97	-	70	58,0	25,0	33,0	318	
	TL 24 H 200	16 F	24	1610	42	97,02	95,65	103	-	73,5	58,0	25,0	33,0	320	
	TL 25 H 200	16 F	25	1610	42	101,06	99,69	106	-	77	58,0	25,0	33,0	321	
	TL 26 H 200	16 F	26	1610	42	105,11	103,73	111	-	82	58,0	25,0	33,0	322	
	TL 27 H 200	16 F	27	1610	42	109,15	107,78	115	-	85	58,0	25,0	33,0	323	
	TL 28 H 200	16 F	28	1610	42	113,19	118,82	119	-	90,5	58,0	25,0	33,0	325	
	TL 30 H 200	16 F	30	1610	42	121,28	119,90	127	-	98	58,0	25,0	33,0	327	
	TL 32 H 200	16 F	32	2012	50	129,36	127,99	135	-	106	58,0	25,0	26,0	328	
	TL 36 H 200	17 F	36	2012	50	145,53	144,16	152	102	121	58,0	32,0	26,0	334	
	TL 40 H 200	17 F	40	2012	50	161,70	160,33	168	106	138	58,0	32,0	26,0	338	
	TL 44 H 200	17 F	44	2012	50	177,87	176,50	184	106	152	58,0	32,0	26,0	339	
TL 48 H 200	17 F	48	2517	60	194,04	192,67	200	119	169	58,0	45,0	13,0	342		
FUNDICION	TL 60 H 200	20	60	2517	60	242,55	241,18	-	119	223	60,0	45,0	7,5	-	
	TL 72 H 200	20	72	2517	60	291,06	289,69	-	119	270	60,0	45,0	7,5	-	
	TL 84 H 200	20	84	2517	60	339,57	338,20	-	119	320	60,0	45,0	7,5	-	
	TL 96 H 200	20	96	2517	60	388,08	386,71	-	119	366	60,0	45,0	7,5	-	
	TL 120 H 200	20	120	2517	60	485,10	483,73	-	119	462	60,0	45,0	7,5	-	

### H 300 Paso 1/2"

Material	CODIGO	TIPO	DIENTES	CASQUILLO	INTERIOR MAXIMO	Dp	De	Df	Dm	Di	F	L	R	N.º VALONA	Kg.
ACERO	TL 20 H 300	18 F	20	1215	42	80,85	79,48	87	-	64,5	84,0	38,0	23,0	315	
	TL 21 H 300	18 F	21	1215	42	84,89	83,52	91	-	65	84,0	38,0	23,0	316	
	TL 22 H 300	18 F	22	1615	42	88,94	87,56	93	-	67	84,0	38,0	23,0	317	
	TL 23 H 300	18 F	23	1615	42	92,98	91,61	97	-	70	84,0	38,0	23,0	318	
	TL 24 H 300	18 F	24	1615	42	97,02	95,65	103	-	73,5	84,0	38,0	23,0	320	
	TL 25 H 300	18 F	25	1615	42	101,06	99,69	106	-	77	84,0	38,0	23,0	321	
	TL 26 H 300	18 F	26	1615	42	105,11	103,73	111	-	82	84,0	38,0	23,0	322	
	TL 27 H 300	18 F	27	2012	50	109,15	107,78	115	-	85	84,0	32,0	26,0	323	
	TL 28 H 300	18 F	28	2012	50	113,19	118,82	119	-	90,5	84,0	32,0	26,0	325	
	TL 30 H 300	18 F	30	2012	50	121,28	119,90	127	-	98	84,0	32,0	26,0	327	
	TL 32 H 300	18 F	32	2517	60	129,36	127,99	135	-	106	84,0	45,0	19,5	328	
	TL 36 H 300	18 F	36	2517	60	145,53	144,16	152	-	121	84,0	45,0	19,5	334	
	TL 40 H 300	18 F	40	2517	60	161,70	160,33	168	-	138	84,0	45,0	19,5	338	
	TL 44 H 300	19 F	44	2517	60	177,87	176,50	184	119	152	86,0	45,0	20,5	339	
	TL 48 H 300	19 F	48	2517	60	194,04	192,67	200	119	169	86,0	45,0	20,5	342	
	FUNDICION	TL 60 H 300	20	60	2517	60	242,55	241,18	-	119	223	86,0	45,0	20,5	-
TL 72 H 300		20	72	2517	60	291,06	289,69	-	119	270	86,0	45,0	20,5	-	
TL 84 H 300		20	84	2517	60	339,57	338,20	-	119	320	86,0	45,0	20,5	-	
TL 96 H 300		20	96	3030	75	388,08	386,71	-	150	362	86,0	76,0	5,0	-	
TL 120 H 300		20	120	3030	75	485,10	483,73	-	150	460	86,0	76,0	5,0	-	